
Product Data Sheet



Description: The Holding Tank Level Sender is used in mainly black or grey water tanks. Can also be used in freshwater tanks.

Connector:	Delphi, Tyco, or others are available according to customer's requirements upon request
IP Rating:	IP 67
Length Range:	4", 6", 8", 12", 16", 18", 20", 22", 24", 28", & 38" (can be customized)
Material:	SS316 Stainless Steel
Max Current:	500mA
Mounting:	NPT 1.5" thread twist-in, with standard 6 hole thread flange plate, standard 6 hole under ring and 6 piece of M5x30 screws
Operating Temperature:	-40°F ~ +185°F (-40°C ~ +85°C)
Output Signal:	240 – 33Ω or 0 – 190Ω
Rated Power:	125mW
Indicating Range:	10~40mm
Wire:	PVC material (PA corrugated pipe cover is optional)



Sensing Quality, Gauging Success!

3350 Davie Road, Suite 203

Davie, FL 33314

(954) 463-1075

www.kus-usa.com

www.kusauto.com/en

Part Number

American Standard (1.5" NPT)

SHS				SHST			
Length	Part Number	Length	Part Number	Length	Part Number	Length	Part Number
4"	26400			4"	26401		
6"	26405			6"	26406		
8"	26410			8"	26411		
12"	26420			12"	26421		
16"	26430			16"	26431		
18"	26434			18"	26435		
20"	26444			20"	26445		
22"	26448			22"	26449		
24"	26452			24"	26453		
28"	26460			28"	26461		
38"	26492			38"	26493		